

JVS-ND7004-PD01

4CH POE H.265 NVR



Key Features

- Adopt the new VStar GUI, easy to operate and run smoothly
- Support intelligent coding VSmart, greatly reducing storage space
- Improved compatibility for HDD. Support max. of 10TB
- Support Intelligent Detection and Human Detection
- Support 4PoE + 4 Non-PoE access (Total of 8 Cameras)

Description



Index	Description	Index	Description
1	POWER	(5)	VGA
2	IEEE802.3af PoE	6	HDMI
3	RJ45	0	USB
(4)	Audio Out		

Specifications

Model	JVS-ND7004-PD01			
Video & Audio				
IP Camera Input	4CH PoE + 4CH Non-PoE			
Audio Input/ Output	1 Channel 3.5mm Jack Output,			
•	8 Channel Audio output through HDMI			
Display	4 LIDMI 4 MOA			
Interface	1 HDMI, 1 VGA HDMI: 3840x2160, 1920x1080, 2560x1440, 1440x900,			
	1280x1024, 1280x720, 1024x768			
Resolution	VGA: 1920x1080, 1440x900, 1280x1024, 1280x720,			
	1024x768			
Max Decoding	8CH 5.0MP/ 4.0MP/ 1080p/ 960p/ 720p @25fps			
Multi-screen Display	Port Binding 1/4			
aiti ooroon biopiay	Non-port Binding 1/ 4/ 5/ 6/ 7/ 8/ 9			
OSD	Camera Name & Time, Recording, Alarm Detecting,			
Remote connection, Volume, Channel Number Recording				
Compression	H.265/H.264			
Resolution				
Record Mode	Manual, Schedule, Motion Detection			
Video Detection & Alarn				
Trigger Events				
Video Detection	Recording, Snapshot, PTZ, Voice, E-mail, Client, Buzzer Motion Detection, No Video Detection			
Playback & Backup	Wotion Detection, No video Detection			
<u> </u>				
Sync Playback Search Mode	2CH 5.0MP/ 3CH 4.0MP/ 4CH 3.0MP			
Search Mode	Time /Date, Schedule, Motion Detection			
Playback Function	Day View, Hour View, Back Step, Rewind, Pause, Play, Fast Forward, Slow, Step, Full Screen, Snap, Sound			
T laybaok T allotton	On/Off. Zoom			
Backup Mode	FAT32 USB Device/ Network			
Network & Interfaces				
Interface	1 RJ45 Port (10/100/1000Mbps)			
PoE Interface	4x Port 100Mbps IEEE802.3af PoE			
Network Function	TCP/IP, DHCP, UDP, SMTP, NTP, CloudSEE			
Smart Phone	Support iOS, Android App			
Interoperability	ONVIF 2.4			
Storage				
SATA	1 SATA interface			
Capacity	Up to 10TB			
USB	2x USB			
General				
Power Supply	52V DC			
Consumption	≤50W (Without HDD)			
Working Temperature	-10°C ~ 55°C			
Working Humidity	10% ~ 90%			
Dimensions	260x219x45mm			
Weight	≤1.05Kg (Without HDD)			
	=			