

JVS-ND6606-HD


6CH H.265 NVR



Key Features

- Adopt the new VStar GUI, easy to operate and run smoothly
- Support intelligent coding VSmart, greatly reducing storage space
- Improved compatibility for HDD. Support max. of 10TB
- Support Intelligent Detection and Human Detection

Description



Index	Description	Index	Description	
1	RJ45	4	HDMI	
2	Audio Out	5	USB]
3	VGA	6	Power]

Specifications

Model	JVS-ND6606-HD			
Video & Audio				
IP Camera Input	6 Channel			
Audio Input/ Output	1 Channel 3.5mm Jack Output,			
Display	6 Channel Audio output through HDMI			
Interface 1 HDMI, 1 VGA				
Internace	HDMI: 2560x1440, 1920x1080, 1440x900,			
	1280x1024, 1280x720, 1024x768			
Resolution	VGA: 1920x1080, 1440x900, 1280x1024, 1280x720, 1024x768			
Max Decoding	6CH 5.0MP/ 4.0MP/ 1080p/ 960p/ 720p @25fps			
Multi-Screen Display	1/ 4/ 5/ 6			
OSD	Camera Name & Time, Recording, Alarm Detecting, Remote connection, Volume, Channel Number			
Recording				
Compression	H.265/H.264			
Resolution	6CH 5.0MP/ 4.0MP/ 1080p/ 960p/ 720p			
Record Mode	Manual, Schedule, Motion Detection			
Video Detection & Alarm				
Trigger Events	Recording, Snapshot, PTZ, Voice, E-mail, Client, Buzzer			
Video Detection	Motion Detection, No Video Detection			
Playback & Backup				
Sync Playback	1CH 5.0MP, 1CH 4.0MP, 1CH 3.0MP, 2CH 1080p			
Search Mode	Channel Number / Recording Type / Date			
Playback Function	Day View, Hour View, Back Step, Rewind, Pause, Play, Fast Forward, Slow, Step, Full Screen, Snap, Sound On/Off, Zoom			
Backup Mode	FAT32 USB Device/ Network			
Network & Interfaces				
Interface	1 RJ45 Port (10/100Mbps)			
Network Function	TCP/IP, DHCP, UDP, SMTP, NTP, CloudSEE			
Smart Phone	Support iOS, Android App			
Interoperability	ONVIF 2.4			
Storage				
SATA	1 SATA Interfaces			
Capacity	Up to 10TB			
USB	2x USB			
General				
Power Supply	DC 12V			
Consumption	≤10W (Without HDD)			
Working Temperature	-10°C ~ 55°C			
Working Humidity	10% ~ 90%			
Dimensions	255x41x195mm			
Weight	≤1.0kg (Without HDD)			

©2022 Jovision Technology Co., Ltd. All rights reserved. www.jovisionsecurity.com Note: Design and specifications are subject to change without notice. Under no circumstances, this document shall be reproduced, distributed or changed partially or wholly without formal authorization of Jovision Technology Co., Ltd

info@jovision.com