

JVS-XD2504-FC10T

4CH 5MN XVR



Key Features

- TVI / AHD / DVR / NVR / CVI 5-in-1 function, multi-mode input, support HD analog video encoding, support HD analog + HD network video input, support pure HD network video input.
- Supports various mobile phone monitoring (iPhone Android).
- Support multiple web browsers (IE / Chrome / Firefox / Safari).
- Support VGA,HDMI output at the same time.
- Support STVI function.
- Support coaxial audio
- Support multi-languauge

Description



① ALARM ② REC ③ POWER ① ② ③



Index	Description	Index	Description
①	Video In	⑥	RJ45
②	Video Out	⑦	USB
③	HDMI	⑧	Power
④	Audio In	⑨	VGA
⑤	Audio Out		

Specifications

Model	JVS-XD2504-FC10T
System	
Compression	H.265
O/S	Embedded Linux O/S
Video and Audio	
Video Input	4CH,BNC
Preview Ability	4*5MN@20fps (4 in 1) 4*4MN@25fps (4 in 1) 4*1080N@25fps (4 in 1)
Coding Ability	4*5MN@12fps (4 in 1) 4*4MN@17fps (4 in 1) 4*1080N@15fps (4 in 1)
Decoding Ability	4*5MN@12fps (4 in 1) 4*4MN@17fps (4 in 1) 4*1080N@15fps (4 in 1)
Video Output	1CH VGA;1CH HDMI
Channel Mode	Support any channel mode combination (5MN analog + 1080P digital)
Audio In & Out	1/1, RCA
Video Standard	PAL/NTSC
Storage	
SATA	1x SATA Interface
Capacity	Up to 8TB Max.
File Format	H.264、H.265、AVI
Backup Mode	USB
Playback and Backup	
Video Playback	Auto/Timing/ Motion detection
Sync Playback	4CH
Search Mode	Point-in-time search, Calendar search, Event search, Channel search
Network	
Ethernet	10/100 Mbps,1 RJ45
Network Function	TCP/IP, DHCP, DDNS, NTP, SMTP
Interoperability	ONVIF Standard
Smart Phone	iPhone, Android
Hardware	
Network Interface	1x RJ45
USB Interface	2x USB2.0
PTZ Interface	Support RS485 PTZ
Controlling Device	Mouse
Alarm Input	Not Support
Alarm Output	Not Support
Special	
Multi-Screen Display	1/4
Alarm Method	Email Alarm
Digital Zoom	Not Support
Two-Way Talk	Support
Alarm Snapshot	Support
Intelligent Analysis	Support Motion Detection、Video Tampering、Video loss
General	
Power Supply	DC12V/2A
Consumption	≤8W (without HDD)
Working Temperature	-10°C ~60°C
Working Humidity	10% ~ 90% Humidity
Dimensions	250x223x42mm
Weight	800g